

Air Filter

Mini Type


Series F200A

ANSSION
PNEUMATIC & HYDRAULIC

◆ How to Order



Symbol



F200A — 02 N C H B

Nil	Without bracket
B	With bracket

Drain type

Nil	Semi-auto.
H	Manual

Filtration

Nil	5 μ m	C	40 μ m
-----	-------	---	--------

Thread

Nil	G	N	NPT
-----	---	---	-----

Port size

01	1/8	02	1/4
----	-----	----	-----

Air Filter

F200A	Polycarbonate body
-------	--------------------

◆ Specifications

Model	F200A-01	F200A-02
Port size	1/8(option)	1/4(standard)
Fluid	Air	
Body material	Polycarbonate	
Bowl material	Polycarbonate(standard), Anti-acid & alkali(option)	
Filtration	5 μ m(standard), 40 μ m(option)	
Set pressure range	0.05~0.8 MPa	
Max. Inlet pressure(standard)	0.8 MPa	
Max. flow rate	1900l/min	
Ambient and fluid temperature	-10℃~60℃(No freezing)	
Recommended lubricant	Turbin oil class 1(ISO VG32)	
Filter bowl capacity	35cc	
Standard drain	Semi-automatic drain(below 0.05MPa)	
Net weight	245g	

◆ Dimensions

