

Preparation unit—Accessories

AIRTAC

Pressure gauge

■ Specification

Model	GS-40 GF-40 GU-40	GS-50 GF-50 GU-50	GF-60 GU-60	GS-40L GF-40L GU-40L	GS-50L GF-50L GU-50L	GF-60L GU-60L
Fluid	Air					
Port size	1/8"	1/4"	1/4"	1/8"	1/4"	1/4"
Temperature range	-20~60℃					
Accuracy grade	2.5					
Type	Standard type			Lower pressure type		
The pressure range of units and instructions	M	0~1.0MPa			0~0.4MPa	
	B	0~10 bar			0~4 bar	
	P	0~140psi			0~60psi	
	Z	0~10kgf/cm² and 0~140psi(Dual-scale display)			0~4kgf/cm² and 0~60psi(Dual-scale display)	
Material of major parts	Shell: SPCC ; Core: Brass					



■ Ordering code

G S 40 L □

Model	G: Pressure gauge	Scale	Blank: MPa P: psi B: bar Z: Double scale(psi、kgf/cm ²)
Mount Type Code	S: Standard Mount F: Flange Mount U: Pannel Mount	Type code	Blank: Standard L: Lower pressure
Dial diameter	40: OD 40mm 50: OD 50mm 60: OD 60mm		



■ Dimensions

GS Series





Model	A	B	C	D	E
GS-40	42	11	24.5	38.5	1/8"
GS-50	52	14	26.5	44.5	1/4"

GF Series



Model	A	B	C	D	E	F	G	H
GF-40	42	11	24.5	40.5	1/8"	60	52.5	3.4
GF-50	52	14	27.5	47.5	1/4"	71	62	4.4
GF-60	62	14	30	50	1/4"	82	71.5	4.4

GU Series



Model	A	B	B1	C	D	E	F(max)	G	H
GU-40	42	11	7	28	43.5	1/8"	5	21	24.5
GU-50	52	14	8	30.5	50	1/4"	7	24	35
GU-60	62	14	8	30.5	50	1/4"	7	25	35



Gauge

■ Symbol



■ Product feature

1. It has sensitive reaction and can work under low pressure.
2. The displayed words in the dial are clear and there are several pressure units to be selected.
3. There are several installation ways and installing accessories to be selected.
4. Various dimensions of screw thread are available.