

## สายลม

| รุ่น US/UE                                                                        | รุ่นสินค้า | ขนาดสาย |      | สาย<br>หนา | ความ<br>ยาว | แรงดัน<br>ใช้งาน | แรงดัน<br>ทดสอบ | มุมที่<br>สายงอ | น้ำหนัก<br>100M | อุณหภูมิ<br>ใช้งาน | สีของสาย                                     | ชนิดของสาย                                                   |
|-----------------------------------------------------------------------------------|------------|---------|------|------------|-------------|------------------|-----------------|-----------------|-----------------|--------------------|----------------------------------------------|--------------------------------------------------------------|
|                                                                                   |            | OD      | ID   |            |             |                  |                 |                 |                 |                    |                                              |                                                              |
|  | US98A4025  | 4.0     | 2.5  | 0.75       | 200         | 8.0              | 36.0            | 10              | 0.99            | -20 ~ +70          | BK : ดำ<br>C : ใส<br>OR : ส้ม<br>B : น้ำเงิน | - Ester Base<br>Shore A98 ±2<br>- Ester Base<br>Shore A95 ±2 |
|                                                                                   | US98A6040  | 6.0     | 4.0  | 1.00       | 200         | 11.0             | 33.0            | 15              | 1.93            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A8050  | 8.0     | 5.0  | 1.50       | 100         | 12.0             | 36.0            | 15              | 3.77            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A8055  | 8.0     | 5.5  | 1.25       | 100         | 9.00             | 27.0            | 20              | 3.26            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A8060  | 8.0     | 6.0  | 1.00       | 100         | 8.00             | 24.0            | 25              | 2.70            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A1065  | 10.0    | 6.5  | 1.75       | 100         | 10.0             | 30.0            | 20              | 5.58            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A1080  | 10.0    | 8.0  | 1.00       | 100         | 5.50             | 16.5            | 40              | 3.48            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A1280  | 12.0    | 8.0  | 2.00       | 100         | 10.0             | 30.0            | 30              | 7.72            | -20 ~ +70          |                                              |                                                              |
|                                                                                   | US98A1210  | 12.0    | 10.0 | 2.00       | 100         | 9.00             | 27.0            | 65              | 10.81           | -20 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A4025  | 4.0     | 2.5  | 0.75       | 200         | 11.0             | 33.0            | 10              | 0.99            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A6040  | 6.0     | 4.0  | 1.00       | 200         | 10.0             | 30.0            | 15              | 1.93            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A8050  | 8.0     | 5.0  | 1.50       | 200         | 11.0             | 33.0            | 15              | 3.77            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A8055  | 8.0     | 5.5  | 1.25       | 200         | 8.00             | 24.0            | 20              | 3.26            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A8060  | 8.0     | 6.0  | 1.00       | 200         | 7.00             | 21.0            | 25              | 2.70            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A1065  | 10.0    | 6.5  | 1.75       | 200         | 9.00             | 27.0            | 20              | 5.58            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A1080  | 10.0    | 8.0  | 1.00       | 200         | 5.00             | 15.0            | 40              | 3.48            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A1280  | 12.0    | 8.0  | 2.00       | 200         | 9.00             | 27.0            | 30              | 7.72            | -40 ~ +70          |                                              |                                                              |
|                                                                                   | UE95A1210  | 12.0    | 10.0 | 2.00       | 200         | 8.00             | 24.0            | 65              | 10.81           | -40 ~ +70          |                                              |                                                              |
| สายลม PU                                                                          |            |         |      |            |             |                  |                 |                 |                 |                    |                                              |                                                              |

| รุ่น UCS                                                                            | รุ่นสินค้า   | ขนาดสาย |     | แรงดัน<br>ใช้งาน | แรงดัน<br>ทดสอบ | มุมที่<br>สายงอ | ความ<br>ยาว | อุณหภูมิ<br>ใช้งาน | สีของสาย                                     | ชนิดของสาย                                                   |
|-------------------------------------------------------------------------------------|--------------|---------|-----|------------------|-----------------|-----------------|-------------|--------------------|----------------------------------------------|--------------------------------------------------------------|
|                                                                                     |              | OD      | ID  |                  |                 |                 |             |                    |                                              |                                                              |
|  | UCS98A80505  | 8.0     | 5.0 | 12.0             | 36.0            | 22 หรือ 35      | 5           | -20 ~ +70          | BK : ดำ<br>C : ใส<br>OR : ส้ม<br>B : น้ำเงิน | - Ester Base<br>Shore A98 ±2<br>- Ester Base<br>Shore A95 ±2 |
|                                                                                     | UCS98A80508  | 8.0     | 5.0 | 12.0             | 36.0            | 22 หรือ 35      | 8           | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A805012 | 8.0     | 5.0 | 12.0             | 36.0            | 38              | 12          | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A805015 | 8.0     | 5.0 | 12.0             | 36.0            | 38              | 15          | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A10656  | 10.0    | 6.5 | 9.0              | 27.0            | 50              | 6           | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A10658  | 10.0    | 6.5 | 6.5              | 27.0            | 50              | 8           | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A106510 | 10.0    | 6.5 | 6.5              | 27.0            | 50              | 10          | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A106512 | 10.0    | 6.5 | 6.5              | 27.0            | 50              | 12          | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A12806  | 12.0    | 8.0 | 10.0             | 3.0             | 60              | 6           | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A12808  | 12.0    | 8.0 | 10.0             | 3.0             | 60              | 8           | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A128010 | 12.0    | 8.0 | 10.0             | 3.0             | 60              | 10          | -20 ~ +70          |                                              |                                                              |
|                                                                                     | UCS98A128012 | 12.0    | 8.0 | 10.0             | 3.0             | 60              | 12          | -20 ~ +70          |                                              |                                                              |
| สายลมสปริง                                                                          |              |         |     |                  |                 |                 |             |                    |                                              |                                                              |